

As another novelty we have developed a MODULE ARRANGEMENT for our lengthways rotary drum cutters, so that these cutters can be used now more universally.

Consequently your company can operate this milling cutter in the following areas of application:

- building of channels and wells
- sounding and soil preparation
- drilling for ground loosening
- pile head repair
- direct production of drill piles of 150 mm Ø up to 1300 mm Ø (depending on module arrangement)

We offer:

	ER 250-4L Net price €	ER 400L Net price €	ER 700-3L Net price €	ER 1500-3L Net price €	ER 2000L Net price €
Engine	on request	on request	on request	on request	on request
Module	on request	on request	on request	on request	on request
Cutting head	on request	on request	on request	on request	on request
Transition (power torsion head to worm)	on request	on request	on request	on request	on request
Bore worm	on request	on request	on request	on request	on request

Short version: performance data, diameters and weights						
	spezif.	ER 250 L	ER 400 L	ER 700 L	ER 1500 L	ER 2000 L
Rotations		75 - 90	60	70	60	65
Oil quantity G		40 bis max. 130	100 bis max. 170	130 bis max. 230	200 bis max. 380	250 bis max. 500
Working pressure p max.	bar	320	320	320	320	320
Torque max.	Nm	3190 - 4752	7936 - 9504	8896 - 10688	16000 - 21376	21247 - 25521
Excavator weight group	Tons	3-15	7-20	15-25	25-45	35-45
Recommended engine power of carrier	kw	20-70	50-90	65-110	110-190	130-190